



Sump Pump	Power rating (kW)	Weight (kg)	Width (mm)	Height (mm)	Solids Passage (mm)	Outlet (inch)
1. Maxi L	30	285	506	1302	15	8
2. Maxi N	37	280	506	1302	15	8
3. Maxi H	37	240	436	1046	12	4
4. Maxi SH	37	270	440	1148	12	4
5. Magnum L	57	540	750	1475	12	10
6. Magnum N	57	540	750	1475	12	8
7. Magnum H	57	540	750	1475	12	6



# Electric Sump Pump Specification Sheet 2 of 2

WJ Groundwater operate one of the largest fleets of electrical sump pumps in the Middle East. At the core of WJ fleet are the Grindex drainage sump pumps, a heavy duty pump ideal for construction dewatering. It is robust, power efficient and can be used for pumping dirty water and sewage.

Discharge flows range from 5l/s to 350l/s, and head capacity range from 15m to 100m. Low head (L), standard (N) and high head (H) versions are available. The sump pumps connect to a remote starter panel and are powered by generators or 3-phase mains power.

See 'Specification Sheet 1' for medium capacity electrical sump pumps. Contact us today for further information.

\*Available for hire with starter panel, discharge hose, power cable, generators, alarms, float-switch, operator and pontoon raft.

